

ADDENDUM No. 1
September 4, 2020

Subject: Village of Antioch 2020 Resurfacing Program
Section Number: 21-00000-01-GM
September 10, 2020 Letting

To Prospective Bidders:

Revision to the Notice to Bidders:

1. The proposal submittal and bid opening date and time have been revised to September 10, 2020 at 11:15 AM, therefore
 - **Replace the “Notice to Bidders” form from the original proposal booklet with the enclosed revised “Notice to Bidders”.**

Revision to the Project Quantities:

1. The project quantities have been revised to include the additional pay items for sidewalk improvements along Lake Street, therefore
 - **Replace the “Schedule of Prices, BLR 12200a” from the original proposal booklet with the enclosed revised “Schedule of Prices, BLR 12200a”.**
 - **Replace the “Schedule of Quantities” from the original proposal booklet with the enclosed revised “Schedule of Quantities”.**

Revision to the Special Provisions:

1. The special provisions for “Bollards” and “Trench Channel Drain” have been added to the proposal booklet, therefore
 - **The enclosed special provision pages for “Bollards” and “Trench Channel Drain” shall be added to the original “Special Provisions”.**

Contractors must utilize the enclosed material when preparing their bid. The signed copy of ADDENDUM No. 1 must be included with the submitted Proposal.

No Proposal shall be considered responsive nor shall any Proposal be considered unless the appropriate space for acknowledgement of the addendum is completed in the original bid package and unless the Proposal is accompanied by a signed copy of this ADDENDUM No. 1. The signed copy of ADDENDUM No. 1 shall be attached to the Proposal.

The undersigned agrees to be bound by the modifications made within this ADDENDUM No. 1, and hereby waives any and all claims based upon the additional or modified information contained herein.

Acknowledgement of ADDENDUM No. 1

Company Name: _____

Signature of Company Representative: _____

RETURN WITH BID

NOTICE TO BIDDERS

County Lake
Local Public Agency Antioch
Section Number 21-00000-01-GM
Route Various

Sealed proposals for the improvement described below will be received at the office of Village of Antioch,
874 Main Street, Antioch, IL, 60002 until 11:15 AM on September 10, 2020
Address Time Date

Sealed proposals will be opened and read publicly at the office of Village of Antioch,
874 Main Street, Antioch, IL, 60002 at 11:15 AM on September 10, 2020
Address Time Date

DESCRIPTION OF WORK

Name 2020 Maintenance Resurfacing Program Length: 11175.00 feet (2.12 miles)
Location Various Locations
Proposed Improvement HMA surface removal, polymerized binder course, hot-mix asphalt surface course,
curb and gutter removal and replacement, etc.

1. Plans and proposal forms will be available in the office of HR Green, Inc., 420 N. Front St, McHenry, IL, 60050
Available electronically by contacting Tina Napolitano at tnapolitano@hrgreen.com or at 815-385-1778
Address

2. [X] Prequalification
If checked, the 2 low bidders must file within 24 hours after the letting an "Affidavit of Availability" (Form BC 57), in duplicate, showing all uncompleted contracts awarded to them and all low bids pending award for Federal, State, County, Municipal and private work. One original shall be filed with the Awarding Authority and one original with the IDOT District Office.

3. The Awarding Authority reserves the right to waive technicalities and to reject any or all proposals as provided in BLRS Special Provision for Bidding Requirements and Conditions for Contract Proposals.

- 4. The following BLR Forms shall be returned by the bidder to the Awarding Authority:
a. BLR 12200: Local Public Agency Formal Contract Proposal
b. BLR 12200a Schedule of Prices
c. BLR 12230: Proposal Bid Bond (if applicable)
d. BLR 12325: Apprenticeship or Training Program Certification (do not use for federally funded projects)
e. BLR 12326: Affidavit of Illinois Business Office

5. The quantities appearing in the bid schedule are approximate and are prepared for the comparison of bids. Payment to the Contractor will be made only for the actual quantities of work performed and accepted or materials furnished according to the contract. The scheduled quantities of work to be done and materials to be furnished may be increased, decreased or omitted as hereinafter provided.

6. Submission of a bid shall be conclusive assurance and warranty the bidder has examined the plans and understands all requirements for the performance of work. The bidder will be responsible for all errors in the proposal resulting from failure or neglect to conduct an in depth examination. The Awarding Authority will, in no case be responsible for any costs, expenses, losses or changes in anticipated profits resulting from such failure or neglect of the bidder.

7. The bidder shall take no advantage of any error or omission in the proposal and advertised contract.

8. If a special envelope is supplied by the Awarding Authority, each proposal should be submitted in that envelope furnished by the Awarding Agency and the blank spaces on the envelope shall be filled in correctly to clearly indicate its contents. When an envelope other than the special one furnished by the Awarding Authority is used, it shall be marked to clearly indicate its contents. When sent by mail, the sealed proposal shall be addressed to the Awarding Authority at the address and in care of the official in whose office the bids are to be received. All proposals shall be filed prior to the time and at the place specified in the Notice to Bidders. Proposals received after the time specified will be returned to the bidder unopened.

9. Permission will be given to a bidder to withdraw a proposal if the bidder makes the request in writing or in person before the time for opening proposals.



SCHEDULE OF PRICES

A bid will be declared unacceptable if neither a unit price nor total price is shown.

County LAKE
 Local Public Agency ANTIOCH
 Section 21-00000-01-GM
 Route VARIOUS

Schedule for Multiple Bids

Combination Letter	Sections Included in Combinations	Total

Schedule for Single Bid

(For complete information covering these items, see plans and specifications)

Bidder's Proposal for making Entire Improvements
--

Item No.	Items	Unit	Quantity	Unit Price	Total
1	BITUMINOUS MATERIALS (TACK COAT)	POUND	24,746		
2	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-4.75, N50	TON	1,700		
3	HOT-MIX ASPHALT SURFACE COURSE, MIX 'D', IL-9.5, N50	TON	4,130		
4	HOT-MIX ASPHALT SURFACE REMOVAL, BUTT JOINT	SQ YD	91		
5	HOT-MIX ASPHALT SURFACE REMOVAL, 2 INCH	SQ YD	3,330		
6	HOT-MIX ASPHALT SURFACE REMOVAL, 2-1/4 INCH	SQ YD	5,285		
7	HOT-MIX ASPHALT SURFACE REMOVAL, 2-3/4 INCH	SQ YD	10,500		
8	HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH 1-1/2 TO 2-1/4 INCH	SQ YD	18,655		
9	LONGITUDINAL JOINT SEALANT	FOOT	10,235		
10	PAVEMENT PATCHING (PARTIAL DEPTH), 3 INCH	SQ YD	546		
11	PAVEMENT PATCHING (PARTIAL DEPTH), 6 INCH	SQ YD	210		
12	DRIVEWAY PAVEMENT REMOVAL	SQ YD	398		
13	HOT-MIX ASPHALT DRIVEWAY PAVEMENT, 3"	SQ YD	398		
14	DRIVEWAY BRICK PAVER REMOVAL AND REPLACEMENT	SQ FT	78		
15	SUBBASE GRANULAR MATERIAL, TYPE B, 4"	SQ YD	55		
16	SIDEWALK REMOVAL	SQ FT	1,380		
17	CURB REMOVAL	FOOT	50		
18	PORTLAND CEMENT CONCRETE SIDEWALK REMOVAL AND REPLACEMENT	SQ FT	1,400		
19	PORTLAND CEMENT CONCRETE SIDEWALK, 5"	SQ FT	310		
20	COMBINATION CONCRETE CURB AND GUTTER, VARIABLE HEIGHT	FOOT	70		
21	CONCRETE GUTTER, TYPE B (SPECIAL)	FOOT	285		
22	COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT	FOOT	3,580		
23	AGGREGATE SHOULDERS, TYPE B	TON	46		
24	AGGREGATE BASE COURSE REMOVAL AND REPLACEMENT, 12 INCH	SQ YD	381		
25	DRAINAGE & UTILITY STRUCTURES TO BE ADJUSTED	EACH	32		
26	DRAINAGE & UTILITY STRUCTURES TO BE RECONSTRUCTED	EACH	15		
27	FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)	EACH	30		
28	VALVE BOXES TO BE ADJUSTED	EACH	19		
29	LIDS AND GRATES	EACH	5		
30	RAISED REFLECTIVE PAVEMENT MARKER REMOVAL	EACH	18		
31	RAISED REFLECTIVE PAVEMENT MARKER	EACH	18		
32	THERMOPLASTIC PAVEMENT MARKING, LETTERS & SYMBOLS	FOOT	126		
33	THERMOPLASTIC PAVEMENT MARKING, 4"	FOOT	6,090		
34	THERMOPLASTIC PAVEMENT MARKING, 6"	FOOT	1,100		
35	THERMOPLASTIC PAVEMENT MARKING, 12"	FOOT	905		
36	THERMOPLASTIC PAVEMENT MARKING, 24"	FOOT	145		
37	SEEDING, SPECIAL	SQ YD	287		
38	SHORT TERM PAVEMENT MARKING, 4" (SPECIAL)	FOOT	630		
39	TRENCH CHANNEL DRAIN	FOOT	40		
40	BOLLARDS	EACH	8		
41	DETECTOR LOOP REPLACEMENT	FOOT	231		
42	TRAFFIC CONTROL AND PROTECTION, STANDARD 701501	L SUM	1		
43	TRAFFIC CONTROL AND PROTECTION, STANDARD 701701	L SUM	1		
44	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM	1		

BOLLARDS

Description.

This item shall consist of furnishing and installing a concrete filled steel bollard along Lake Street at location determined by the Village.

Materials and Construction Requirements.

The bollard shall be 6" diameter schedule 40 steel mounted at 36" above grade with a 48" minimum burial depth. The bollard shall be installed in an 18" diameter drilled hole. The hole shall be backfilled with concrete along with the interior of the pipe. The top of pipe shall have concrete constructed and shaped to have a domed top.

Measurement and Basis of Payment.

This work shall be paid for at the contract unit price per each for BOLLARDS.

TRENCH CHANNEL DRAIN

Description.

This work shall consist of furnishing and installing a trench drain system along Lake Street as directed by the Engineer. The work includes all necessary excavation, frames, grates, fittings, coupling systems, connections, concrete collars, concrete backfill, and accessories.

Materials.

Trench drain shall be manufactured by Neenah, R-4996-A6 frame with slotted ADA compliant grate or approved equal. Frames shall be secured to the surrounding concrete backfill and shall provide sufficient pullout resistance of trench drain frame. Grates may be either integral with the trench drain or removable. However, a minimum of 24 inches removable grates shall be provided at the end points of the trench drain. Curb opening end caps per manufacturer specifications shall be provided at the upstream and downstream end of the trench drain run to maintain existing flows between adjacent existing curb and gutter.

Construction Requirements.

The trench drain system shall be installed in accordance with the manufacturer's installation instructions and drawings.

Trench drains shall be installed in a trench excavated to the lines and grades established by the Engineer. Excavate a trench that will ensure a minimum concrete thickness of 6 inches along the bottom and 6 inches along each side. Excavation shall conform to Section 202 of the Standard Specifications.

Grade and prepare a firm and uniform trench bottom throughout the entire length of the trench drain system. Remove all obstructions and debris from the trench excavation prior to backfilling. Join the trench drain sections according to the recommendations of the manufacturer. Furnish sections that are closely jointed and secured to prevent separation of the trench drain during backfilling.

Trench drains shall be positioned in the excavated trench so that, when finished, the surrounding concrete backfill will be a minimum of 1/8 inch and a maximum of 3/16 inch above the level of the trench drain frame. In no case shall the frame or grate of the trench drain extend above the level of the surrounding sidewalk.

Place concrete backfill in the trench against undisturbed material at the sides and bottom of the trench in a manner that will prevent floating or shifting of the trench drain, and will prevent voids in, or segregation of the concrete. Tamp and spade to prevent honeycombing. Remove any foreign material that falls into the trench prior to or during placement of concrete. Concrete shall conform to Section 353 of the Standard Specifications.

Furnish a textured surface on the concrete that is even with the adjacent surface with a broom or burlap drag to produce a durable skid-resistant surface.

Measurement and Basis of Payment.

This work will be measured and paid for at the contract unit price per foot, for TRENCH CHANNEL DRAIN.